

## JT-Q2144

# B-ISDN Signalling ATM Adaptation Layer (SAAL) - Layer Management for the SAAL at the Network Node Interface (NNI)

### 1. Relations with international standards

This Standard conforms to the ITU-T Recommendation Q.2144 approved at ITU-T SG11 meeting in April-May, 1995.

### 2. Summary of departures from ITU-T Recommendations

#### 2.1 Optional items

None.

#### 2.2 National items

None.

#### 2.3 Others

- (1) This Standard has nothing to precede the above ITU-T Recommendation.
- (2) The items listed below are deleted from the above ITU-T Recommendation.

- (a) APPENDIX II

- (b) MAAL-LOCAL\_PROCESSOR\_OUTAGE.request  
MAAL-LOCAL\_PROCESSOR\_RECOVERED.request

- (c) signalling link proving

They have been deleted for the following reasons.

- (a) is deleted because it is not required at this time.

- (b) is deleted because it's also removed in JT-Q2140.

- (c) is deleted because it's also removed in JT-Q704.

Some of the items that has specified not in this standard but in the above ITU-T Recommendation are shown with # to support comprehension.

- (3) The item below is added to the above ITU-T Recommendation (shown with \* in the text).

- (a) the signal MAAL-REPORT.indication (-, -, SREC) in Figure 5-1

This is added for the following reason.

- (a) is added for the conformance of Figure 5-1 and Table 6-1.

- (4) This standard has nothing that differ from the above ITU-T Recommendation.

### 3. The history of revised versions

Version	Date	Outline
1	1996	Established