

JT-G960
Digital Section for ISDN Basic Rate Access

1.Relations to international standards

This standard is based on ITU-T Recommendation G.960(WTSC-93).

2.Amendments and modifications

- (1) In this standard, the following items are modified in the above recommendation.
- (a) In § 5.4.1. i)DS1.X and A.3.1 i)ET1.X,
"FIGURE 1/I.414" is incorrect, and changed to "FIGURE 1/I.411.

3. History of revision

Version	History of Revision Dates	Remarks
Version 1	1990.11	Established
Version 2	1993.11	Revised

4.Others

- (1) Items for further study
- (a) Definition of DS2.X state supporting a loopback function (§ 5.4.1.1).
 - (b) Test condition for activation time (§ 5.5).
 - (c) Definition, control and procedures for the auxiliary equipment line switchover functions (§ 6.2.2).
 - (d) Control of functions in NT1 (§ 6.2.3).
 - (e) System-dependent status report functions (§ 6.3.6).
 - (f) Definition of the state transition for loopback into ET layer 1 state machine (TABLE A-2 in ANNEX A, TABLE B-2 in ANNEX B).

(2) References:

TTC Standards : JT-I411, JT-I430, JT-Q920, JT-Q921 and JT-G961

ITU-T Recommendations : G.960, Q.512, Q.940, I.603, G.821, G.801, I.350, G.114, I.112, I.412, I.430 and G.701