JT-H331

Broadcasting type audiovisual multipoint systems and terminal equipment

< References >

1. Relations with international standards

This standard covers technical requirements for the broadcasting type multipoint system and terminal equipment which allow the audiovisual signal from a transmitting terminal to be distributed to multiple receiving terminals by utilizing signal distribution function of the ISDN digital switches, and conforms to the ITU-T recommendation H.331 which is approved in the World Telecommunication Standardization Conference (WTSC-93) held in March 1993.

(NOTE)

The term "CCITT" in this standard should be replaced as shown below in accordance with the result of the World Telecommunication Standardization Conference (WTSC-93) in March 1993.

• CCITT recommendation => ITU-T recommendation

• Organization of CCITT => ITU-TS

• CCITT general assembly in March 1993 => World Telecommunication Standardization Conference

(WTSC-93)

2.Departures from the above international recommendation

2.1 Optional items

None

2.2 National matter items

None

2.3 Others

- (1) Concerning the 64kbit/s PCM voice coding and channel rates, this standard refer to the ITU-T recommendation, not the TTC standard, because both A-law and μ -law, and the channel rates of 1920kbit/s have to be taken into account.
- (2) The items described as "under study" or "subject for further study" in this standard, will be standardized taking the ITU-T study progress into consideration.

2.4 Differences from the above ITU-T recommendation on the framework

None

3. Up-dating

Version	Date	Contents
First version	April 27, 1993	Enactment

4. Others

(1) References

TTC standards : JT-G722, JT-G728

JT-H221, JT-H230, JT-H242, JT-H261, JT-H320

JT-O931

ITU-T recommendation: G.711

H.200/AV.253 I.400 Series