Broadband ISDN (B-ISDN) Functional Description of the B-ISDN User Part (B-ISUP) of Signalling System No. 7

1. Relations with international standards

This Standard conforms the Recommendation Q.2761 approved for the ballot at ITU-T SG11 plenary meeting in September 1994.

2. Summary of departures from ITU-T Recommendations

2.1 Optional items

None.

2.2 National items

None

2.3 Others

- (1) This Standard has no items that go ahead of those in ITU-T Recommendations.
- (2) The following items are deleted from the above ITU-T Recommendation:
 - (a) Forward address signalling Overlap operation
 - (b) Descriptions for international gateway exchanges
 - (c) ASEs for supplementary services in Figure 1-1/JT-Q2761
 - (d) Some functions/services in Table 5-1/JT-Q2761
- (e) Relationships to other Standards/Recommendations and some descriptions for references They are deleted for the following reasons:
 - (a) This is because it is not required in national standard.
 - (b) This is because it is defined for international connection.
 - (c) This is because Recommendations for supplementary services were not approved when this Standard was first specified.
 - (d) This is because it is not required in national standard.
 - (e) This is because there are some Recommendations which have not yet standardized.
- (3) The following items are modified from the above Recommendation:
 - (a) Subclause 1.1 and note in clause 2 are modified to adapt this Standard.
- (4) In this Standard, no deletion nor modification is made to simple segmentation in clause 5 and services assumed from the MTP in clause 6 because MTP for B-ISUP is under study in ITU-T.

2.4 Comparison of chapter composition between the ITU-T Recommendation and this Standard

There is no deference in chapter composition with the above ITU-T Recommendation.

3. The History of revised versions.

Version	Date	Outline
1	April, 27, 1995	Established

4. Others

None.